

Technical Data Sheet (TDS)

TAF Cheetah

Homopolymers emulsion

TAF 25 PVA (Polyvinyl Acetate)



DESCRIPTION

Polyvinyl Acetate Homopolymer water based



APPLICATIONS

- It is particularly suitable for the preparation of adhesive for wood and paper
- It can be used in the building sector to make parquet adhesives in bookbinding.
- It used in the textile industry as stiffening and sizing agent.
- It shows excellent permanent elasticity.
- It has high stability and good compatibility with plasticizers



PROPERTIES

Property	Value
Viscosity at 23°C by Brookfield Spindle 6	80000 ± 10000
Solid content	25 ± 1%
pH value	4.5 ± 5.5

Density at 23°C	1.05-1.08gm/ cm ³
Minimum temperature for film formation	14
Prevailing particle size range	0.6

TAF-25 Can be adjusted based on the customer's request

SHELF LIFE & STORAGE

- **Shelf life:** 18 months at 30°C when stored under recommended conditions.
- **Storage Conditions:** Store indoors in original, unopened containers at temperature between 3°C and 30°C.

PACKING OPTIONS

- 125-150 kg in plastic drums.
- 30 kg in plastic drums .
- 3 kg in plastic Gallon



☎ +966567675330

✉ admin@tafaulchem.com

🌐 tafaulchem.com

